

Oil Wipe Stains



194 Pre-matched colors available on demand!

Wood Finishers **DEPOT**
professional finishing & touchup supplies 

woodfinishersdepot.com | 1.866.883.3768

Oil Wipe Stains

Oil Wipe Stains are formulated with resins that offer the working characteristics of an oil stain, but provide the rapid dry benefits with less than a one hour recoat time! Oil Wipe Stains are available in a clear base and a wide selection of 194 pre-matched colors on demand. Oil Wipe Stains are tintable with Industrial Colorants or our Super Penetrating NGR Stains. This stain provides an exceptionally clean appearance with an increased depth of color and vibrancy that provides interior wood with a distinctive warm and rich appearance.

ADVANTAGES

Regulatory

- HAPs Compliant

Application

- User Friendly - Spray or brush Application
- Mild Odor
- Quick Recoat time - 1 Hour Dry Time!
- 194 Pre-matched Colors Available On Demand
- Specifically Formulated for Our High Performance Wood Coatings

Tintability

- Tintable with Industrial Colorants
- Tintable with our Super Penetrating NGR Stains

Availability

- one gallon • five gallon • 55 gallon

CUSTOM COLORS AVAILABLE

194 Pre-matched Colors Available On Demand. Your salesperson can provide a stain deck showing colors on birch and oak wood for choosing colors.



KT1000 Stain Decks available for purchase



USES

Oil Wipe Stain provides an exceptionally clean appearance with an increased depth of color and vibrancy that provides interior wood with a distinctive warm and rich appearance.

This product can be applied by brush or spray gun. It is packaged ready-to-spray..

Oil Wipe Stain

TECHNICAL DATA

Material Preparation

Thoroughly agitate before and during use to prevent settling of color pigments.

Application

When spraying use low pressure and apply a full wet coat. After an initial flash, wipe and blend evenly with a lint-free, natural-fiber cloth to minimize a muddy effect and to allow even color distribution with a glazed, uniform appearance. Do Not Dry Rag! When using a rag or brush, apply liberally and blend evenly. Cover only small areas at a time.

Clean Up

Use LT300 Lacquer Thinner to clean all equipment. Dispose of dirty solvent and cleaning rags in a safe and approved manner. Solvent or stain soaked rags should be stored in water-filled, closed containers prior to disposal. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

customer service: 866.883.3768
woodfinishersdepot.com

